

Ultra Prime

PRODUCT DESCRIPTION AND USES:

Ultra-Prime is a premium quality all-purpose marine primer based on selected oils, alkyd resins and lead free pigments. Used as a primer for interior and exterior use on bare timber surfaces, for above and below water service where improved water resistance is required.

PHYSICAL PROPERTIES:

Colour:	Pink
Gloss Level:	Flat
Volume Solids:	51%
Product Density:	1.30Kg / litre
Drying Time @ 25°:	Touch dry 2 hours Hard dry 16 hours Recoat 16 hours (min) Recoat 24 hours (max)

APPLICATION DATA:

Suitable for application by brush roller or spray.

Recommended

Dry Film Thickness: 75um

Theoretical Spreading Rate
@ 75um:

6.5 sq metres per litre

Thinning: Not required for brush or roller application. For spray application up to 20% of T-72 thinner may be added.

Equipment Cleaning: Clean all equipment immediately after with T-72 Thinner

SURFACE PREPARATION:

Remove all loose and flaking paint back to bare timber. Desalination and clean down of all surfaces should be actioned by a thorough washing and scrub down using detergent and hot water in sufficient strength to remove all traces of oil and grease. Repeated applications should be undertaken as necessary until all surfaces are absolutely clean. Allow surface to dry completely before priming. A practical way to check for dryness of the prepared timber surfaces is to sprinkle them with French chalk or talcum powder and note any local darkening of the powder over a period of several hours.

STORAGE AND PACKING:

Storage: The Product must be stored in accordance with national regulations. Preferred storage conditions are to keep the containers in a dry space provided with adequate ventilation. The containers should be sealed tightly.

Packing content: 1 Litre, 2 Litre 4 Litre.

HEALTH AND SAFETY:

Please observe the precautionary notices displayed on the containers. Spray under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on skin should be removed with suitable cleaner, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, please refer to the Material Safety Data Sheet.

DISCLAIMER: *The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data with out notice.*

*ISSUED SEPTEMBER 2009.
THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED.*



Pyramid Paints - Seahorse Marine Paints - 26/B Coburg Road Alberton South Australia 5014
Phone (08) 83411337 - Fax (08) 3411385